


ABB Motors and Generators		Technical Data Sheet				
		Project	Location			
Department/Author		Customer name		Customer ref.		
Our ref.		Rev/Changed by <b>A</b>		Date of issue <b>1/18/2019</b>		
		Saving ident <b>untitled.xls</b>		Item name <b>1.00001</b>		
				Pages <b>1(3)</b>		
No.	Definition	Data	Unit	Remarks		
1	Product	<b>TEFC, 3-phase, squirrel cage induction motor</b>				
2	Product code	<b>3GBA 102 520-BDDIN</b>		Calc. ref.	3GZH021010-2	
3	Type/Frame	<b>M2BAX 100LB 4</b>				
4	Mounting	<b>IM3001, B5(flange)</b>				
5	Rated output $P_N$	<b>2.2</b>	kW			
6	Service factor	<b>1</b>				
7	Type of duty	<b>S1 100%</b>				
8	Rated voltage $U_N$	<b>415</b>	VD	+10, -10 %		
9	Rated frequency $f_N$	<b>50</b>	Hz	+5, -5 %		
10	Rated speed $n_N$	<b>1445</b>	r/min			
11	Rated current $I_N$	<b>4.8</b>	A			
12						
13	Starting current $I_s/I_N$	<b>7</b>				
14	Nominal torque $T_N$	<b>14.5</b>	Nm			
15	Locked rotor torque $T_s/T_N$	<b>2.9</b>				
16	Maximum torque $T_{max}/T_N$	<b>3.7</b>				
17						
18						
Load characteristics		Load %	Current A	Efficiency %	Power factor	
19	PLL determined from residual loss	<b>100</b>	<b>4.8</b>	<b>86.7 / IE3</b>	<b>0.74</b>	
20		<b>75</b>	<b>4</b>	<b>86.9</b>	<b>0.66</b>	
21		<b>50</b>	<b>3.4</b>	<b>85.1</b>	<b>0.53</b>	
22						
23	Thermal withstand time hot	<b>7</b>	s			
24	Thermal withstand time cold	<b>13</b>	s			
25	Insulation class / Temperature class	<b>F / B</b>				
26	Ambient temperature	<b>50</b>	°C			
27	Altitude	<b>1000</b>	m.a.s.l.			
28	Degree of protection	<b>IP55</b>				
29	Cooling system	<b>IC411 self ventilated</b>				
30	Bearing DE/NDE	<b>6206-2Z/C3 - 6205-2Z/C3</b>				
31	Sound pressure level (LP dB(A) 1m)	<b>70</b>	dB(A)	at no-load		
32	Moment of inertia $J = \frac{1}{4} GD^2$	<b>0.00919</b>	kg-m2			
33	Position of terminal box	<b>Top</b>				
34	Direction of rotation	<b>Bi-directional</b>				
35	Weight of rotor	<b>8</b>	kg			
36	Total weight of motor	<b>34</b>	kg			
37						
38						
39						
40						
41						
42						
43						
44						
45						
Ex-motors						
46						
47						
48						
Option Variant Codes / Definition						
49						
50						
51						
52						
Remarks:						
Data based on situation 12/21/2015						

All performance values are subject to IS/IEC tolerances

