

| ABB Motors and Generators           |                                                        | Technical Data Sheet                         |                            |  |
|-------------------------------------|--------------------------------------------------------|----------------------------------------------|----------------------------|-------------------------------------------------------------------------------------|
| Project                             |                                                        | Location                                     |                            |                                                                                     |
| Department/Author                   |                                                        | Customer name                                |                            | Customer ref.                                                                       |
| Our ref.                            |                                                        | Rev/Changed by<br>A                          | Date of issue<br>6/15/2019 | Saving ident<br>m2bax_ie2_2_4_6_8p_foot cum flar                                    |
|                                     |                                                        |                                              |                            | Item name<br>4.00003                                                                |
|                                     |                                                        |                                              |                            | Pages<br>1(3)                                                                       |
| No.                                 | Definition                                             | Data                                         | Unit                       | Remarks                                                                             |
| 1                                   | Product                                                | TEFC, 3-phase, squirrel cage induction motor |                            |                                                                                     |
| 2                                   | Product code                                           | 3GBA 314 210-HDCIN                           |                            |                                                                                     |
| 3                                   | Type/Frame                                             | M2BAX 315SMA 8                               |                            |                                                                                     |
| 4                                   | Mounting                                               | IM2001, B35(foot-flange)                     |                            |                                                                                     |
| 5                                   | Rated output P <sub>N</sub>                            | 55                                           | kW                         |                                                                                     |
| 6                                   | Service factor                                         | 1                                            |                            |                                                                                     |
| 7                                   | Type of duty                                           | S1 100%                                      |                            |                                                                                     |
| 8                                   | Rated voltage U <sub>N</sub>                           | 415                                          | VD                         | +10, -10 %                                                                          |
| 9                                   | Rated frequency f <sub>N</sub>                         | 50                                           | Hz                         | +5, -5 %                                                                            |
| 10                                  | Rated speed n <sub>N</sub>                             | 743                                          | r/min                      |                                                                                     |
| 11                                  | Rated current I <sub>N</sub>                           | 112                                          | A                          |                                                                                     |
| 12                                  | Method of Starting                                     | DOL                                          |                            |                                                                                     |
| 13                                  | Starting current I <sub>s</sub> /I <sub>N</sub>        | 7                                            |                            |                                                                                     |
| 14                                  | Nominal torque T <sub>N</sub>                          | 707                                          | Nm                         |                                                                                     |
| 15                                  | Locked rotor torque T <sub>s</sub> /T <sub>N</sub>     | 1.7                                          |                            |                                                                                     |
| 16                                  | Maximum torque T <sub>max</sub> /T <sub>N</sub>        | 2.9                                          |                            |                                                                                     |
| 17                                  |                                                        |                                              |                            |                                                                                     |
| 18                                  |                                                        |                                              |                            |                                                                                     |
| Load characteristics                |                                                        | Load %                                       | Current A                  | Efficiency %                                                                        |
| 19                                  | PLL determined from residual loss                      | 100                                          | 112                        | 91                                                                                  |
| 20                                  |                                                        | 75                                           | 87.6                       | 91                                                                                  |
| 21                                  |                                                        | 50                                           | 102                        | 89                                                                                  |
| 22                                  |                                                        |                                              |                            |                                                                                     |
| 23                                  | Thermal withstand time hot                             | 12                                           | s                          |                                                                                     |
| 24                                  | Thermal withstand time cold                            | 22                                           | s                          |                                                                                     |
| 25                                  | Insulation class / Temperature class                   | F / B                                        |                            |                                                                                     |
| 26                                  | Ambient temperature                                    | 50                                           | °C                         |                                                                                     |
| 27                                  | Altitude                                               | 1000                                         | m.a.s.l.                   |                                                                                     |
| 28                                  | Degree of protection                                   | IP55                                         |                            |                                                                                     |
| 29                                  | Cooling system                                         | IC411                                        |                            |                                                                                     |
| 30                                  | Bearing DE/NDE                                         | 6319/C3 - 6316/C3                            |                            |                                                                                     |
| 31                                  | Sound pressure level (LP dB(A) 1m)                     | 85                                           | dB(A)                      | at no-load                                                                          |
| 32                                  | Moment of inertia J = ¼ GD2                            | 3.2                                          | kg-m2                      |                                                                                     |
| 33                                  | Position of terminal box                               | Top                                          |                            |                                                                                     |
| 34                                  | Direction of rotation                                  | Bi-directional                               |                            |                                                                                     |
| 35                                  | Weight of rotor                                        | 234                                          | kg                         |                                                                                     |
| 36                                  | Total weight of motor                                  | 830                                          | kg                         |                                                                                     |
| 37                                  |                                                        |                                              |                            |                                                                                     |
| 38                                  |                                                        |                                              |                            |                                                                                     |
| 39                                  |                                                        |                                              |                            |                                                                                     |
| 40                                  |                                                        |                                              |                            |                                                                                     |
| 41                                  |                                                        |                                              |                            |                                                                                     |
| 42                                  |                                                        |                                              |                            |                                                                                     |
| 43                                  |                                                        |                                              |                            |                                                                                     |
| 44                                  |                                                        |                                              |                            |                                                                                     |
| 45                                  |                                                        |                                              |                            |                                                                                     |
| Ex-motors                           |                                                        |                                              |                            |                                                                                     |
| 46                                  |                                                        |                                              |                            |                                                                                     |
| 47                                  |                                                        |                                              |                            |                                                                                     |
| 48                                  |                                                        |                                              |                            |                                                                                     |
| Option Variant Codes / Definition   |                                                        |                                              |                            |                                                                                     |
| 49                                  | Application check not made in absence of load details. |                                              |                            |                                                                                     |
| 50                                  | Efficiency level : IE2 as per IS12615 2018.            |                                              |                            |                                                                                     |
| 51                                  |                                                        |                                              |                            |                                                                                     |
| 52                                  |                                                        |                                              |                            |                                                                                     |
| Remarks:                            |                                                        |                                              |                            |                                                                                     |
| Applicable standards: IS 12615 2018 |                                                        |                                              |                            |                                                                                     |

All performance values are subject to IS/IEC tolerances





